

OPTIMA THERMAL RECEIPT PRINTER P200



Compact & Reliable

The Optima P200 is a small compact Thermal Receipt Printer uses 57mm (2 1/4") paper size, the same size paper rolls as credit card and debit rolls. It's engineered for reliability to meet the demands of retailers large and small. Perfect for commercial retail and restaurant applications, and existing sites that are only compatible with serial printers.

Designed for efficiency

Designed and conceived to suit any and all environments, the Optima P200 is equipped with quality components allowing it to achieve fast print speeds with low-noise and low power consumption all at an affordable price.



Light & Portable

The lightweight and compact design allows workers to carry and operate the printer with ease in any kind of environments including retail, restaurant, and industrial sites.

Optional Ports Available

The P200 is a reliable printer that comes standard with a serial port. A USB or Ethernet port are available on custom orders.

Drop-in-Paper loading

A simple drop-in-paper loading means that even inexperienced operators can easily maintain and load paper rolls with minimum of effort.

Key Features

- ✓ Standard Serial Port (USB/ Ethernet available)
- ✓ 57mm (2 1/4") paper size
- ✓ Perfect for Retail, Restaurant and Industrial applications
- ✓ Also perfect for existing sites only compatible with serial printers
- ✓ Lightweight and easy to carry
- ✓ High-quality thermal printing
- ✓ Minimal-noise and High-speed printing
- ✓ Supports cash drawer connection
- ✓ Easy paper-roll installation,
- ✓ Low power consumption(Eco-Friendly)

Printer

Print Method: Thermal line printing

Print Speed: 70mm/second

Print Parameters: Download Logo trademark supported

Print Width: 57.5 x 0.5mm

Print Diameter: 75mm

Print Thickness: 0.06-0.08mm

Print Command: Compatible with Esc/POS

Cutter: Without Paper Cutter

Character: 384dots/line,ANK characture

Font:A:12*24dots,1.5(W)*3.0(H)mm

Simplified/Traditional:24x24dots, 3.0(W)x3.0(H)mm

Specifications

Dimensions: (D) 215 x (W) 110 x (H)136mm

Weight: 2.60kg

Interface Connectivity

Serial port (Standard)

USB (Custom Order)

Ethernet (Custom Order)

General Features

Power: DC24V/2.5A

Reliability Print: 100km

Temperature: 0-45°C

Contrast Humidity: 10-80°C

Drivers: Windows 7 , Windows 10 , Windows 11

Certificate: CE FCC CCC ISO9001:2008

Barcode type: JAN13(EAN13)/JAN8(EAN8)/CODE39